

Pressure Max

Heavy Duty Pressure Washing Formula

- Cleans Engines, Parts, and Vehicles
- Use with High or Low Pressure, Hot or Cold Water
- Nonflammable, Noncorrosive, and Nonbutyl
- HMIS #1 Health Rating and Contains Biodegradable Surfactants

Heavy Duty Pressure Washing Formula

PIF#2513

DESCRIPTION

Pressure Max delivers maximum performance in a myriad of cleaning situations. Based on unique surfactants and chelants, Pressure Max easily removes grease, grime and other deposits. Using little or no agitation, this high powered product cleans leaving surfaces free of residue. The product can be used with high or low pressure, hot or cold water. Pressure is extremely safe for the worker, surfaces and the environment, making it great to use in a wide variety of applications.

DIRECTIONS

Dilute appropriately in hot or cold water and apply with low or high pressure. Always rinse thoroughly with clear water. Follow the dilution chart for the most effective cleaning:

- Light Duty Cleaning ----- 1:128 (1oz per gallon)
- Medium Duty Cleaning ----- 1:85 (1.5oz per gallon)
- Heavy Duty Cleaning ----- 1:64 (2oz per gallon)
- Very Heavy Duty Cleaning ----- 1:32 (4oz per gallon)

ADVANTAGES

- Cleans All Parts of Engines, Parts and Vehicles
- Excellent with High or Low Pressure, Hot or Cold Water
- Non-flammable, Non-corrosive and Non-butyl
- Contains Biodegradable Surfactants
- Non-phosphate
- HMIS #1 Health Rating

RECOMMENDED APPLICATIONS

Pressure Washing	Engine Cleaning	Fifth Wheels
Vehicle Frames	Tires & Wheels	Shop Floors
Metal Parts	Rubber & Plastic	Glass
Fleet Operations	Maintenance Garages	Repair Shops

TYPICAL PRODUCT SPECIFICATIONS

Appearance -----	Clear liquid
Color -----	Colorless
pH -----	7.0
Weight, per U.S. gallon -----	9.1 lbs.
Specific gravity -----	1.09
Viscosity -----	Thin
Foam -----	Very low
Flashpoint -----	None
Emulsification -----	Excellent
Stability -----	Excellent
Solubility -----	Complete
DOT shipping -----	Non-hazardous

