



PneumaSeal™

Prevents Flat Tires

Guaranteed for the Life of the Tire®

DESCRIPTION

PneumaSeal HD was scientifically developed to eliminate flat tires in a variety of applications. Patented tire sealant technology enables PneumaSeal HD to quickly and effectively seal tread area punctures up to ¼ inch in diameter. PneumaSeal HD also seals and prevents air loss from bead leaks, rim leaks and tire porosity. The unique thixotropic formula of PneumaSeal enables it to maintain an even layer of sealant around the inner liner of the tire, which allows for immediate sealing of any tread area puncture. PneumaSeal HD has been thoroughly tested in laboratories studies and in field trials plus PneumaSeal HD is guaranteed to prevent flat tires for the life of the tire.

ADVANTAGES

- Prevents flat tires.
- Reduces fuel costs by maintaining the recommended tire pressure.
- Prevents under-inflation due to slow leaks or punctures.
- Continuously coats interior casing to fill cracks.
- Reduces internal dry rot and deterioration by keeping tire casing moist and pliable.
- Protects against rust and corrosion.
- Maximizes and extends tire life by more than 20% by maintaining proper tire inflation and pulling excess heat away from the tread area.
- Seals rim weld imperfections.
- Reduces the risk of tire blowouts.
- Ready to use – requires no mixing, stirring, shaking or other special preparation.

RECOMMENDED APPLICATIONS

Agriculture equipment	Industrial (fork lifts, skid loaders, etc.)
All Terrain Vehicles (ATVs)	Lawn & Garden tractor after market
Automobiles	Lawn & Garden tractor manufacturers
Bicycles	Light Duty Trucks
Common carriers	Medium Duty Trucks (up to 26,000 GVW)
Community service fleets (police, fire, etc.)	Military vehicles
Construction	Miscellaneous small wheel vehicles
Consumer	Motorcycles
Delivery vehicles	Off the road vehicles (OTR)
Farm implements	Rental vehicles and equipment
Fleet vehicles	Snow plows and snow blowers
Forestry	Trailers (boats, horse, house, utility)
Golf carts	Wheelchairs
Golf course equipment	Wheelbarrows

TYPICAL PRODUCT SPECIFICATIONS

Appearance -----	Thick green liquid
Scent -----	Slight solvent
Weight, per U.S. gallon -----	8.51 lbs.
Specific gravity -----	1.02
Viscosity -----	Thick (thixotropic)
Flashpoint -----	Non-Flammable
Rinsability -----	Excellent
Stability -----	Excellent
Storage -----	2 year minimum (closed container)
DOT shipping -----	Non-hazardous

AVAILABLE PACKAGE SIZES

275 gallon totes, 55 gallon drums, 5 gallon pails, 12x1 Quart Case & 12x1 Pint Cases



PneumaSeal Products Division, Kor-Chem, Inc.

Atlanta, Georgia 30336 • Toll Free: 1-800-752-6627 • www.pneumaseal.net